


Table of specifications

Meiasol

MC type Magnetic contactors



Frame size				18AF				22AF				
Type				MC-6a	MC-9a	MC-12a	MC-18a	MC-9b	MC-12b	MC-18b	MC-22b	
				●	●	●	●	●	●	●	●	
		Screws clamp terminals										
		Lug clamp terminals										
Number of poles				3pole				3pole				
Rated operational voltage, Ue				690V				690V				
Rated insulation voltage, Ui				690V				690V				
Rated frequency				50/60Hz				50/60Hz				
Rated impulse withstand voltage, Uimp				6kV				6kV				
Maximum operating rate in operating cycles per hour(AC3)				1800 operations per hour				1800 operations per hour				
Durability	Mechanical			15 mil. operations				15 mil. operations				
	Electrical			2.5 mil. operations				2.5 mil. operations				
Current and power	AC-1, Thermal current		A	25	25	25	32	25	27	32	45	
	AC-3	200/240V	kW	2.2	2.5	3.5	4.5	2.5	3.5	4.5	5.5	
			A	9	11	13	18	11	13	18	22	
		380/440V	kW	3	4	5.5	7.5	4	5.5	7.5	11	
			A	7	9	12	18	9	12	18	22	
	500/550V	kW	3	4	7.5	7.5	4	7.5	7.5	15		
			A	6	7	12	13	7	12	13	20	
	690V	kW	3	4	7.5	7.5	4	7.5	7.5	15		
			A	4	5	9	9	6	9	9	18	
	1000V	kW	-	-	-	-	-	-	-	-	-	
			A	-	-	-	-	-	-	-	-	
	Rated Short-time withstand current (IEC 60947)	1s	A	210	250	280	300	250	280	300	400	
10s		A	105	110	120	130	110	120	154	186		
30s		A	70	70	80	85	70	80	100	130		
1min		A	61	61	61	70	61	61	84	90		
3min		A	40	45	47	50	45	50	60	60		
10min		A	30	30	30	40	30	30	40	50		
≥ 15min		A	25	26	28	30	26	28	30	45		
		A	25	25	25	32	25	25	40	40		
UL rating (50/60Hz)	Continuous current		A	25	25	25	32	25	25	40	40	
	Single phase	110~120V	HP	0.5	0.5	0.75	1	0.5	0.75	1	2	
		220~240V	HP	1.5	1.5	2	3	1.5	2	3	3	
	Three phase	200~208V	HP	2	2	3	7.5	2	3	7.5	7.5	
		220~240V	HP	3	3	5	7.5	3	5	7.5	10	
		440~480V	HP	5	5	7.5	10	5	7.5	10	15	
		550~600V	HP	7.5	7.5	10	15	7.5	10	15	20	
	NEMA size			00	00	0	1	00	0	1		
Size and weight		AC control	Weight	kg	0.33				0.34			
			Size(W×H×D)	mm	45×73.5×80.4				45×73.5×87.4			
		DC control	Weight	kg	0.4				0.41			
				45×73.5×96.6				45×73.5×103.6				
Auxiliary(standard)				1a or 1b				1a1b				
Auxiliary		Side mount		UA-1				UA-1				
		Front mount		UA-2, UA-4				UA-2, UA-4				

Note) Minimum conduct current of Auxiliary contactor is DC 17V 5mA.

MT type Thermal Overload Relays



				MT-12/□		MT-32/□	
Type	screws clamp terminals			•		•	
	Lug clamp terminals						
Rated operational voltage, Ue				690V		690V	
Rated insulation voltage, Ui				690V		690V	
Rated impulse withstand voltage, Uimp				6kV		6kV	
Trip class				10A, 20		10A, 20	
Setting range				0.1~18A		0.1~40A	
Size and weight	Weight	kg		0.1		0.17	
		Size(W×H×D)	mm	45×73.2×63.7		45×75×90	

* The safety cover of magnetic contactor and thermal overload relay is optional.

**40AF**

MC-32a	MC-40a
•	•
3pole	
1000V	
1000V	
50/60Hz	
8kV	
1800 operations per hour	
12 mil. operations	
2 mil. operations	
55	60
7.5	11
32	40
15	18.5
32	40
18.5	22
28	32
18.5	22
20	23
22	22
17	17
600	700
260	300
160	190
100	120
70	80
55	65
50	60
50	60
2	3
5	7.5
7.5	15
10	15
20	30
25	30
1P	2
0.55	
69×83×90	
0.77	
69×83×117.1	
2a2b	
UA-1	
UA-2, UA-4	

**MT-32/ □**

•
690V
690V
6kV
10A, 20
0.1~40A
0.17
45×75×90

**65AF**

MC-50a	MC-65a
•	•
•	•
3pole	
1000V	
1000V	
50/60Hz	
8kV	
1200 operations per hour	
12 mil. operations	
2 mil. operations	
100	115
15	18.5
55	65
22	30
50	65
30	33
43	60
30	33
28	35
30	30
23	23
1000	1050
550	700
330	380
250	270
150	200
90	120
87	96
70	100
3	5
10	15
20	25
25	30
40	50
50	60
1.05	
79×106×119	
1.3	
79×106×146.4	
2a2b	
UA-1	
UA-2, UA-4	

**MT-63/ □**

•
•
690V
690V
6kV
10A, 20
4~65A
0.31/0.33
55×81×100

**100AF**

MC-75a	MC-85a	MC-100a
•	•	•
•	•	•
3pole		
1000V		
1000V		
50/60Hz		
8kV		
1200 operations per hour		
12 mil. operations		
2 mil. operations		1 mil. operations
125	135	160
22	25	30
75	85	105
37	45	55
75	85	105
37	45	55
64	75	85
37	45	55
42	45	65
37	37	37
28	28	28
1100	1200	1320
750	800	900
400	450	500
300	350	400
220	270	270
140	170	180
114	150	160
110	135	160
5	7.5	10
15	15	20
25	30	30
30	40	40
50	60	75
60	75	75
	3	
1.93		
94×140×135.8		
2.8		
94×140×172.3		
2a2b		
UA-1		
UA-2, UA-4		

**MT-95/ □**

•
•
690V
690V
6kV
10A, 20
7~100A
0.48/0.5
70×97×110

Table of specifications


Meiasol

MC type Magnetic contactors



Frame size			150AF		225AF		400AF		
Type			MC-130a	MC-150a	MC-185a	MC-225a	MC-265a	MC-330a	MC-400a
	screws clamp terminals		•	•	•	•	•	•	•
	Lug clamp terminals		•	•	•	•			
Number of poles			3pole		3pole		3pole		
Rated operational voltage, Ue			1000V		1000V		1000V		
Rated insulation voltage, Ui			1000V		1000V		1000V		
Rated frequency			50/60Hz		50/60Hz		50/60Hz		
Rated impulse withstand voltage, Uimp			8kV		8kV		8kV		
Maximum operating rate in operating cycles per hour(AC3)			1200 operations per hour		1200 operations per hour		1200 operations per hour		
Durability	Mechanical		5 mil. operations		5 mil. operations		5 mil. operations	2.5 mil. operations	
	Electrical		1 mil. operations		1 mil. operations		1 mil. operations	0.5 mil. operations	
Current and power	AC-1, Thermal current	A	200	250	300	350	400	500	520
	AC-3 200/240V	kW	37	45	55	75	80	90	125
		A	130	150	185	225	265	330	400
	380/440V	kW	60	75	90	132	147	160	200
		A	130	150	185	225	265	330	400
	500/550V	kW	60	70	110	132	147	160	225
		A	90	100	180	200	225	280	350
	690V	kW	55	55	110	140	160	200	250
		A	60	60	120	150	185	220	300
	1000V	kW	75	75	132	132	147	147	147
		A	50	50	90	90	105	105	105
	Rated Short-time withstand current (IEC 60947)								
	1s	A	1350	1800	2000	2500	3500	4000	4600
	10s	A	950	1200	1500	1700	2400	3000	4400
	30s	A	700	800	1000	1200	1500	2500	2974
	1min	A	550	600	800	1000	1100	1700	1846
	3min	A	350	450	520	700	800	1000	1313
	10min	A	200	300	350	500	600	620	760
	≥ 15min	A	175	280	320	400	500	553	699
UL rating (50/60Hz)	Continuous current	A	200	250	300	350	400	500	520
		Single phase 110~120V	HP	10	15	15	-	-	-
		220~240V	HP	20	25	30	-	-	-
	Three phase 220~240V	HP	40	40	60	60	75	100	125
		HP	40	50	60	75	100	100	150
		HP	75	100	125	150	200	200	300
	550~600V	HP	75	75	125	150	200	200	300
		HP							
		HP							
	NEMA size			4			5		
Size and weight	AC control	Weight	2.4		5.4		9.2		
	DC control	Size(W×H×D) mm	119×158×130.3		138×203×185.1		163×243×204.4		
Auxiliary(standard)	Side mount	Weight	2a2b		2a2b		2a2b		
	Front mount	Size(W×H×D) mm	UA-1		AU-100, AU-100E (Max.4a4b)		AU-100, AU-100E (Max.4a4b)		
			UA-2, UA-4		-		-		

MT type Thermal Overload Relays



Type			MT150/ □	MT225/ □	MT400/ □
	screws clamp terminals		•	•	•
	Lug clamp terminals		•	•	•
Rated operational voltage, Ue			690V	690V	690V
Rated insulation voltage, Ui			690V	690V	690V
Rated impulse withstand voltage, Uimp			6kV	6kV	6kV
Trip class			10A, 20	10A, 20	10A, 20
Setting range			34~150A	65~240A	85~400A
Size and weight	Weight	kg	0.67	2.5	2.6
	Size(W×H×D) mm		95×109×113	147×141×184	151×171×198

* The safety cover of magnetic contactor and thermal overload relay is optional.



2650AF			
MC-1400a	MC-1700a	MC-2100a	MC-2650a
●	●	●	●
3pole			
1000V			
1000V			
50/60Hz			
8kV			
300 operations per hour			
0.5 mil. operations		0.3 mil. operations	
0.05 mil. operations		0.02 mil. operations	
1400	1700	2100	2650
290	310	-	-
860	1050	-	-
550	700	900	-
860	1050	1450	-
-	-	-	-
800	1000	-	-
800	950	-	-
-	-	-	-
-	-	-	-
-	-	-	-
8000	10000	10000	-
4500	5500	5500	-
-	-	-	-
2600	3000	3000	-
-	-	-	-
1400	1700	2100	2650
-	-	-	-
-	-	-	-

2a2b
AU-100, AU-100E (Max.4a4b)



MT-800/□
●
690V
690V
6kV
10A, 20
200~800A
11.5
$360 \times 530 \times 212$