

Accessories for TD/TS series up to 800A

Susol

Terminals

Front connection


Terminal mounter




- It is supplied with Susol MCCBs as a standard part of circuit breaker.
- Connecting part with terminal for bus bar, cable with lug

| MCCB | Type |
|-------------------|------|
| TD100,TD160 | TM1 |
| TS100,TS160,TS250 | TM2 |
| TS400,TS630 | - |
| TS800 | - |

Inner box terminal



- Bare cable connectors for Susol TD and TS series circuit breakers
- Can be used for both aluminum and copper cables



| Applicable to | Type | Pole | Set quantity | Cable connection possibilities | Conductor size |
|-----------------|-------------------------|------|--------------|--------------------------------|--------------------------------------|
| TD100, 160 | SBT13 | 3 | 1 Set (3EA) | 1 | L(mm) 21 |
| | SBT14 | 4 | 1 Set (4EA) | | S(mm ²)Cu/Al 2.5~95 |
| | | | | | Tightening torque (kgf · cm) 120~147 |
| TS100, 160, 250 | SBT23 | 3 | 1 Set (3EA) | 1 | L(mm) 21 |
| | SBT24 | 4 | 1 Set (4EA) | | S(mm ²)Cu/Al 10~150 |
| | | | | | Tightening torque (kgf · cm) 120~147 |
| TS400, 630 | IBT ^{Note1} 33 | 3 | 1 Set (3EA) | 1 | L(mm) 30 |
| | IBT34 | 4 | 1 Set (4EA) | | S(mm ²)Cu/Al 70~300 |
| | | | | | Tightening torque (kgf · cm) 367~428 |
| PB12, 13 | IBT ^{Note2} 13 | 3 | 1 Set (3EA) | 1 | L(mm) 18 |
| | | | | | S(mm ²)Cu/Al 2.5~95 |
| | | | | | Tightening torque (kgf · cm) 306 |
| PB22, 23 | IBT ^{Note2} 23 | 3 | 1 Set (3EA) | 1 | L(mm) 21 |
| | | | | | S(mm ²)Cu/Al 10~150 |
| | | | | | Tightening torque (kgf · cm) 306 |

Note) 1. IBT3 for TS630 can be applied in case that rate current is upto 400A.
2. IBT13, 23 are for Plug-in base.

