5F

Couplings

1/2"-2" Brass Construction 2-1/2-4" Stainless Steel construction only

Cl. I, Groups A, B, C, D Cl. II, Groups E, F, G Cl. III Explosionproof
Dust-Ignitionproof
Wet Locations

Applications:

EC couplings are used:

 In hazardous areas where a flexible member is required in a conduit system to accomplish difficult bends, or to allow for movement or vibration of connected equipment or units

Features:

- Rugged design to withstand explosive pressure (Class I)
- Mechanical abuse
- · Liquid-tight for wet locations
- For use where lack of space makes use of rigid conduit difficult
- Wire duct liner in sizes ½" to 2" insulates against grounds and burnthrough from short circuit
- No bonding jumpers required, metallic braid provides continuous electrical path
- ECGJH combination has two threaded male end fittings
- ECLK combination has one female union and one male threaded end fitting

Certifications and Compliances:

• NEC:

 $^{1}\!/_{\!2}"$ and $^{3}\!/_{\!4}"$ (Brass and S516) – Class I, Division 1, Groups A, B, C, D 1" to 2" (Brass and S516) – Class I, Division 1, Groups C, D

All sizes also for use in Class II, Division 1, Groups E, F, G and Class III

• UL Standard: 1203

ATEX and IECEx - ECGJH S516 Only: ½" and ¾" (4" to 36" flexible length only) – Ex d IIC, IP66
 1", 1½", 1½", 2" (4" to 36" flexible length only) – Ex d IIB, IP66

ECGJH (Male connections both ends)

Flexible			Flexible			Flexible		
Length			Length			Length		
(In.)	Size	Cat. #	(In.)	Size	Cat. #	(In.)	Size	Cat. #
4	1/2	ECGJH14	18	1	ECGJH318	27	21/2	ECGJH727
4	3/4	ECGJH24	18	11/4	ECGJH418	27	3	ECGJH827
6	1/2	ECGJH16	18	11/2	ECGJH518	27	4	ECGJH1027
6	3/4	ECGJH26	18	2	ECGJH618	30	1/2	ECGJH130
6	1	ECGJH36	18	21/2	ECGJH718	30	3/4	ECGJH230
8	1/2	ECGJH18	18	3	ECGJH818	30	1	ECGJH330
8	3/4	ECGJH28	18	4	ECGJH1018	30	11/4	ECGJH430
8	1	ECGJH38	21	1/2	ECGJH121	30	11/2	ECGJH530
10	1/2	ECGJH110	21	3/4	ECGJH221	30	2	ECGJH630
10	3/4	ECGJH210	21	1	ECGJH321	30	21/2	ECGJH730
10	1	ECGJH310	21	11/4	ECGJH421	30	3	ECGJH830
12	1/2	ECGJH112	21	11/2	ECGJH521	30	4	ECGJH1030
12	3/4	ECGJH212	21	2	ECGJH621	33	1/2	ECGJH133
12	1	ECGJH312	21	21/2	ECGJH721	33	3/4	ECGJH233
12	11/4	ECGJH412	21	3	ECGJH821	33	1	ECGJH333
12	11/2	ECGJH512	21	4	ECGJH1021	33	11/4	ECGJH433
12	2	ECGJH612	24	1/2	ECGJH124	33	11/2	ECGJH533
12	21/2	ECGJH712	24	3/4	ECGJH224	33	2	ECGJH633
12	3	ECGJH812	24	1	ECGJH324	33	21/2	ECGJH733
12	4	ECGJH1012	24	11/4	ECGJH424	33	3	ECGJH833
15	1/2	ECGJH115	24	11/2	ECGJH524	33	4	ECGJH1033
15	3/4	ECGJH215	24	2	ECGJH624	36	1/2	ECGJH136
15	1	ECGJH315	24	21/2	ECGJH724	36	3/4	ECGJH236
15	11/4	ECGJH415	24	3	ECGJH824	36	1	ECGJH336
15	11/2	ECGJH515	24	4	ECGJH1024	36	11/4	ECGJH436
15	2	ECGJH615	27	1/2	ECGJH127	36	11/2	ECGJH536
15	21/2	ECGJH715	27	3/4	ECGJH227	36	2	ECGJH636
15	3	ECGJH815	27	1	ECGJH327	36	21/2	ECGJH736
15	4	ECGJH1015	27	11/4	ECGJH427	36	3	ECGJH836
18	1/2	ECGJH118	27	11/2	ECGJH527	36	4	ECGJH1036
18	3/4	ECGJH218	27	2	ECGJH627			

Standard Materials and Finishes:

• End fittings:

 $^{1\!/_{\!2}"}$ to 2" – forged brass; natural $2^{1\!/_{\!2}"}$ to 4" – stainless steel; natural

Female unions:

1/₂" to 1" - steel; electrogalvanized with chromate treatment 1/₄" to 4" - Feraloy® iron alloy; electrogalvanized with aluminum acrylic paint

- ½" to 2" have bronze braid covering and flexible brass inner core; packing is woven cotton braid impregnated with asphalt
- 21/2" to 4" have a Type 304 stainless steel braid

Options:


 Description
 Suffix

 All stainless steel (available for ECGJH only)
 \$516

For severely corrosive locations, a flexible PVC protective coating will be supplied

Special coupling lengths available up to 144 inches. To order, change last two digits in any standard catalog number to the two or three digit length desired in whole inches i.e. To order a $\frac{3}{4}$ " trade size 110 inches long, use catalog number ECGJH2110.

Dimensions



Crouse-Hinds