



# Kindorf®

## Conduit, Cable & Pipe Supports

**T&B Catalog Number:**

KCPC150

**UPC Number:**

61601311061

**Status:**

Active

**Description:**

1-1/2 in. Steel King Cobra One-Piece Conduit and Pipe Clamp with GoldGalv finish.

### Features

Superior design load capabilities for industrial applications. Embosses on shoulder and hooks increase loading capability and durability, preventing deformation of clamps.

Durable one-piece, heavy-duty steel construction. Rugged stirrup provides increased strength for heavier loads, minimizing deflection.

Wider saddle design with anti-rotation tabs distributes load evenly over a larger surface area, preventing jacket damage.

Heavy-duty 5/16 in. hex bolt with multi-driver head, Robertson square, Phillips cross-recess and slot, provides a full range of installation options.

One clamp size works on equal trade sizes for both EMT and Rigid conduits, simplifying clamp specification.

### Application

Attaches a full range of EMT, Rigid conduit, Pipe & Cable to Strut Channels.

### General

T&B Replacement Catalog Number	LKCPC150
Material	Steel
Finish	GoldGalv
Static Load Limit (lb)	350
Safety Factor	4

### Dimension Information

Cable O.D. Range (inches)	1.690-1.980
Conduit Size (inches)	1 1/2

### Specifications

3dmodel	Available on Website
---------	----------------------

### Packaging

Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	24.91 lbs. per 100

### Application Support

Product Overview-Finishes & Materials	Available on Website
Product Brochure-LOC-KING Cobra	Available on Website
Product Brochure-King Cobra	Available on Website

## Notes

Safety Factor 4

## Certifications

RoHS Compliance

Yes

## Certifications



**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)